

WARRANTY DURATION MATRIX

Roll goods listed under Base, Interply or Cap columns and separated by a comma are options for system configurations within each respective warranty duration row; these are not intended to be installed together or additively.

APP SYSTEMS WITH BASE SHEET ADHERED

Warranty Duration	Warranty Fee (100 Sq Min)	Insulation/Coverboard	Base	Interply ⁵	Cap	Applicable Specs	Recover
12 years	\$4.00/Sq	Optional ¹	Any approved CertainTeed BUR, SBS, or APP Base Sheet ³	—	Any approved CertainTeed APP Cap Sheet ³	APP-C-2-T, APP-I-2-T	APP-I-2-T Approved
15 years	\$7.50/Sq	Optional ¹		—		APP-C-2-T, APP-I-2-T	APP-I-2-T Approved
20 years	\$7.50/Sq	Double layer, second layer adhered	Flintglas® Ply 4	Flintglas Ply 4		APP-I-3-T	
20 years	\$12.50/Sq	Optional ¹	Black Diamond Base Sheet	Optional	Flintlastic GTA-FR, CoolStar, Flintlastic STA ⁴	APP-C-2-T, APP-I-2-T	Prior approval required by CertainTeed Commercial Roofing Technical Services Department
20 years	\$12.50/Sq	Double layer, second layer adhered	Flintlastic APP Base T, Black Diamond Base Sheet	Optional	Flintlastic GTA, Flintlastic GTA-FR, Flintlastic STA ⁴ , Flintlastic STA Plus ⁴	APP-I-2-T	
20 years	\$12.50/Sq	Optional ¹	Flintlastic Ultra Glass SA, Flintlastic STA	Optional	Flintlastic GTA, Flintlastic GTA-FR, Flintlastic STA ⁴ , Flintlastic STA Plus ⁴	APP-C-2-T, APP-I-2-T	
25 years	\$15.00/Sq	Optional ²	All Weather/Empire Base, Flintlastic Poly SMS, Black Diamond Base Sheet	Flintlastic STA Plus	Flintlastic GTA, Flintlastic GTA-FR, Flintlastic STA Plus ⁴	APP-C-3-T, APP-I-3-T	—
25 years	\$15.00/Sq	Double layer, second layer adhered	Flintlastic Ultra Glass SA, Flintlastic Ultra Poly SMS	Optional	Flintlastic GTA, Flintlastic GTA-FR, Flintlastic STA Plus ⁴	APP-I-2-T	—
25 years	\$15.00/Sq	Double layer, second layer adhered	Black Diamond Base Sheet, Flintlastic Ultra Glass SA	Flintlastic STA	Flintlastic GTA, Flintlastic GTA-FR, Flintlastic STA Plus ⁴	APP-I-3-T	—

1. If "Optional" Insulation/Coverboard is utilized, refer to "APP-I-2-T"
2. If "Optional" Insulation/Coverboard is utilized, refer to "APP-I-3-T"
3. Refer to applicable system specification for approved base and cap sheets.
4. Requires coating of SMARTCOAT 400 Series Coating; proof of recoat required in year 10 and 20.
5. If "Optional" interply is utilized, ply number in specification ID increases by one (i.e APP-I-2-T becomes APP-I-3-T).

WARRANTY DURATION MATRIX

Roll goods listed under Base, Interply or Cap columns and separated by a comma are options for system configurations within each respective warranty duration row; these are not intended to be installed together or additively.

APP SYSTEMS WITH MECHANICALLY ATTACHED BASE SHEET

Warranty Duration	Warranty Fee (100 Sq Min)	Insulation/Coverboard	Base	Interply	Cap	Applicable Specs	Recover
12 years	\$4.00/Sq	Optional ¹	Any CertainTeed BUR, SBS, or APP Base Sheet ³	—	Any CertainTeed APP Cap Sheet ³	APP-IN-2-T, APP-N-2-T	Approved
15 years	\$7.50/Sq	Optional ¹		—		APP-IN-2-T, APP-N-2-T	Approved
15 years	\$7.50/Sq	Optional ²		Flintlastic APP Base T, Black Diamond® Base Sheet		APP-IN-3-T, APP-N-3-T	Approved
20 years	\$12.50/Sq	Optional ²	Glasbase Base Sheet, All Weather/Empire Base Sheet, Flintlastic Base 20, Flintlastic Poly SMS	Flintlastic Ultra Glass SA, Black Diamond® Base Sheet, Flintlastic STA, Flintlastic Ultra Poly SMS	Flintlastic GTA, Flintlastic GTA-FR, Flintlastic STA Plus ⁴	APP-IN-3-T, APP-N-3-T	Prior approval required by CertainTeed Commercial Roofing Technical Services Department
20 years	\$12.50/Sq	Single layer, minimum 1.5" and approved coverboard	CertaFast system with Flintlastic Ultra Poly SMS	—		APP-IN-2-CF	
25 years	\$15.00/Sq	Optional ²	All Weather/Empire Base Sheet, Flintlastic Base 20, Flintlastic Poly SMS	Flintlastic STA Plus, Flintlastic Ultra Glass SA, Flintlastic Ultra Poly SMS	Flintlastic GTA, Flintlastic GTA-FR, Flintlastic STA Plus ⁴	APP-IN-3-T, APP-N-3-T	—

1. If "Optional" Insulation/Coverboard is utilized, refer to "APP-IN-2-T"*
2. If "Optional" Insulation/Coverboard is utilized, refer to "APP-IN-3-T"*
3. Refer to applicable system specification for approved base and cap sheets.
4. Requires coating of SMARTCOAT Series 400 Coating; proof of recoat required in year 10 and 20.