

Fissured
Mineral Fiber

Non-directional, sound-absorbing and blocking utilitarian panel with exceptional value.

APPLICATIONS

- Utility Areas
- Retail Warehouses
- Strip Malls
- Commercial Interior Spaces
- Offices
- Other Commercial Buildings / Space Applications



CUSTOMLINE 224



CUSTOMLINE 448




CUSTOMLINE 812


FEATURES AND BENEFITS

- Non-directional fissured pattern
- Three-dimensional face scoring available in 3 geometric designs with Customline options
- Environmental Product Declaration (EPD) available for this product
- Available in fire-rated (Protectone) version
- Health Product Declaration (HPD) available for this product


SUSPENSION SYSTEM OPTIONS




Trim
15/16 Grid



Reveal
Beveled
15/16 Grid




Narrow Reveal
Corner Bevel
9/16 Grid




Narrow Reveal
Beveled
9/16 Grid
(Customline)


CUSTOMLINE SCORING OPTIONS



24 x 48
224



24 x 48
448



24 x 48
812

LEED® v4	
RECYCLED CONTENT	
CLASS A PROTECTONE®	33% 44%

- EA: Optimize Energy Performance
- EA: Prereq. Min. Energy Performance
- EQ: Interior Lighting
- MR: PBT Source Reduction (Healthcare)
- EQ: Acoustic Performance
- EQ: Prereq. Min. Acoustic Performance (Schools)
- EQ: Low-Emitting Materials
- EQ: Daylight
- MR: Material Ingredients (HPDs)
- MR: Sourcing Raw Materials
- MR: Environmental Product Declarations (EPDs)
- MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.



Fissured
Mineral Fiber

All products in this line feature these attributes:



LR
0.83



EPD
AVAILABLE



HPD
AVAILABLE



EMISSION
COMPLIANT
CERTIFIED



RECYCLED
CONTENT
33-44%

BAROQUE

TRIM



NRC 55

Product	Format	Dimensions (in.)
BET-157	Panels	24 x 24 x 5/8
PBT-157	Panels	24 x 24 x 5/8
BET-197	Panels	24 x 48 x 5/8
PBT-197	Panels	24 x 48 x 5/8
BET-2067	Panels	20 x 60 x 5/8

NRC (UL Classified)	CAC (UL Classified)	Recycled Content	UL Fire-Rated	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet
0.55	33	33%	—	16	64	45	20
0.55	35	44%	Yes*	16	64	70	20
0.55	35	33%	—	8	64	45	20
0.55	40	44%	Yes*	8	64	70	20
0.55	35	33%	—	8	67	52	20

REVEAL



NRC 55

Product	Format	Dimensions (in.)
BET-154	Panels	24 x 24 x 5/8
PBT-154	Panels	24 x 24 x 5/8
BET-194	Panels	24 x 48 x 5/8

0.55	33	33%	—	16	64	45	20
0.55	35	44%	Yes*	16	64	70	20
0.55	35	33%	—	8	64	45	20

NARROW REVEAL



NRC 55

Product	Format	Dimensions (in.)
BET-150	Panels	24 x 24 x 5/8

0.55	33	33%	—	16	64	46	20
------	----	-----	---	----	----	----	----

BAROQUE METRIC

METRIC TRIM



NRC 55

Product	Format	Dimensions (mm)
BET-2067M	Panels	500 x 1500 x 15

NRC (UL Classified)	CAC (UL Classified)	Recycled Content	UL Fire-Rated	Pieces/carton	Sq. m/carton	Lbs./carton	Cartons/pallet
0.55	35	33%	—	8	6	52	20

BAROQUE CUSTOMLINE

REVEAL



NRC 55
NRC 50

Product	Format	Dimensions (in.)
BQCL-224	Panels	24 x 48 x 3/4
BQCL-448	Panels	24 x 48 x 3/4
BQCL-812	Panels	24 x 48 x 3/4
PBQCL-224	Panels	24 x 48 x 3/4

0.55	35	33%	—	8	64	55	16
0.50	35	33%	—	8	64	55	16
0.50	35	33%	—	8	64	55	16
0.50	40	44%	Yes*	8	64	75	16

NARROW REVEAL



NRC 55
NRC 50

Product	Format	Dimensions (in.)
BQCLN-224	Panels	24 x 48 x 3/4
BQCLN-448	Panels	24 x 48 x 3/4
BQCLN-812	Panels	24 x 48 x 3/4

0.55	35	33%	—	8	64	55	16
0.50	35	33%	—	8	64	55	16
0.50	35	33%	—	8	64	55	16

* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

Fissured
Mineral Fiber

PHYSICAL DATA

MATERIAL
Mineral Fiber

ASTM E1264 CLASSIFICATION
Type III, Form 2, Pattern C D - Baroque
Type III, Form 2, Pattern C D K - Customline

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment.

BAROQUE CUSTOMLINE WARRANTY
10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/ceilings.

BAROQUE WARRANTY
1-year Limited Warranty



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com