

SUBMITTAL SHEET

DEEP BOX SERIES

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE: Aluminum

PROFILE Deep Box 2 Deep Box 4 Deep Box 6 Deep Box 8 (.032" thickness only)

COLOR/FINISH Cotton White – #0280 Other: _____
 Natural – #7163

FILLER STRIP Box Flat Recessed Closure – Matte Black – #1883 Open Reveal
 Box Flat Recessed Closure – Cotton White – #0280
* Filler Strip required for all Exterior applications.

ACOUSTICAL BACKER Black Polywrapped Pad
 None
* For use with interior perforated material only.

ACOUSTICAL RATING _____ (NRC – Achieved via Open Reveals)

TRIM Wall Angle Edgeline (interior only) _____
 Floating J-Trim End Caps
Color/Finish# _____

EXPOSURE Interior
 Exterior – Design Wind Pressure (required) _____ PSF

Shop Drawings required on all Exterior projects.

To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
CTSpecialtyCeilings.com

HunterDouglas 
Ceiling & Wall Products
exclusively from CertainTeed

SUBMITTAL SHEET **DEEP BOX SERIES**

SOUND ABSORPTION (NRC) SUMMARY*

Product	Acoustical Infill	NRC
Deep Box 2, non-perforated, open reveal	1" – 1.5 pcf Polywrapped Fiberglass	0.65
Deep Box 2, non-perforated, open reveal	2" – 1.5 pcf Polywrapped Fiberglass	0.90

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting.

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50
- Film on metal: Flame spread: ≤ 25, Smoke ≤ 50
- Wood veneer on metal: Flame spread: ≤ 25, Smoke ≤ 55 (for interior applications)

Weight: Varies 0.5 - 0.75 lbs./sq.ft.

Wind load: Per code (for exterior applications)

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81