

# DIRECTIONAL FISSURED

Fissured  
Mineral Fiber

A directional mineral fiber panel with good acoustical control; an excellent choice for large ceiling areas.




## APPLICATIONS

- Utility Areas
- Retail Warehouses
- Strip Malls
- Commercial Interior Spaces
- Offices
- Other Commercial Buildings / Space Applications

## FEATURES AND BENEFITS

- Environmental Product Declaration (EPD) available for this product
- Available in fire-rated (Protectone) versions
- Health Product Declaration (HPD) available for this product

## SUSPENSION SYSTEM OPTIONS



Trim  
15/16 Grid

LEED® v4	
RECYCLED CONTENT	
CLASS A PROTECTONE®	33% 44%
<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input type="checkbox"/>	EQ: Acoustic Performance
<input type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials
<input checked="" type="checkbox"/>	EQ: Daylight
<input checked="" type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.



# DIRECTIONAL FISSURED

Fissured  
Mineral Fiber

All products in this line  
feature these attributes:



LR  
0.82



EPD  
AVAILABLE



HPD  
AVAILABLE




LOW  
VOC  
EMISSION  
COMPLIANT  
CERTIFIED



RECYCLED  
CONTENT  
33-44%

## DIRECTIONAL FISSURED

	Format	Dimensions (in.)	NRC (UL Classified)	CAC (UL Classified)	Recycled Content	UL Fire-Rated	Pieces/ carton	Sq. Ft./ carton	Lbs./ carton	Cartons/ pallet		
<b>TRIM</b>												
	NRC 55	FH-157	Panels	24 x 24 x 5/8	0.55	33	33%	—	16	64	45	20
		FH-197	Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	45	20
		PFH-157	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	70	20
		PFH-197	Panels	24 x 48 x 5/8	0.55	40	44%	Yes*	8	64	70	20

\* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

## PHYSICAL DATA

### MATERIAL

Mineral Fiber

### ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D

### FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

### MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

### WARRANTY

1-year Limited Warranty. Full warranty information can be found at [certainteed.com/ceilings](http://certainteed.com/ceilings).



## CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)