

Fiber Glass & Rock and Slag Wool Insulation and LEED™

The LEED (Leadership in Energy & Environmental Design) Green Building Rating System™ is a voluntary standard that defines high performance green buildings - which are healthier, more environmentally responsible, and more profitable structures. Credits for certification can be earned in six categories, each with a unique focus on sustainable design: sustainable sites, water efficiency, energy and atmosphere, materials and resources, indoor environmental quality, and innovation and design process.

Specifying fiber glass and rock and slag wool insulation can put you on the right track for LEED certification. The charts below list the LEED categories/prerequisites where fiber glass and rock and slag wool insulation can contribute in 1) new commercial buildings (LEED-NC), 2) existing commercial buildings (LEED-EB) and 3) residential (LEED Homes Pilot Program).

LEED COMMERCIAL (NC)/EXISTING BUILDING (EB)

These credits and prerequisites apply to both LEED-NC and LEED-EB unless otherwise noted.

LEED™ PREREQUISITES & CREDITS	CONTRIBUTION	POINTS
Energy & Atmosphere EA Prerequisite 2: Minimum Energy Performance. Mandatory. "Design the building envelope, HVAC, lighting, and other systems to maximize energy performance. The ASHRAE 90.1-2004 User's Manual contains worksheets that can be used to document compliance with this prerequisite." EA Credit 1: Optimize Energy Performance "Achieve increasing levels of energy performance above the baseline in the prerequisite standard to reduce environmental and economic impacts associated with excessive energy use."	Fiber glass and rock and slag wool insulation help reduce building energy demand. Facilitates compliance with ASHRAE 90.1-2004 and local energy codes.	10 Possible Points (Points depend on energy saved)
Materials & Resources MR Credit 2.1 (LEED-NC Only): Construction Waste Management: Divert 50% From Disposal. Consider recycling cardboard, metal, brick, acoustical tile, concrete, plastic, clean wood, glass, gypsum wallboard, carpet and insulation. MR Credit 2.2 (LEED-NC Only): Construction Waste Management: Divert 75% From Disposal. MR Credit 2.1-2.5 (LEED-EB Only): Optimize Use of Alternative Materials. One point (up to a maximum of five) will be awarded for each 10% of total purchases over the performance period (on a dollar basis) that achieve reduced environmental impact.	Reuse or recycle insulation to help divert 50% of waste from landfills. Fiber glass and rock and slag wool batts can be reused in some circumstances and can be recycled if the infrastructure exists.	1 Point in addition to MR Credit 2.1 1 - 5 Points
MR Credit 4.1 (LEED-NC Only): Recycled Content: 10% MR Credit 4.2 Recycled Content: 20%	Fiber glass contains upwards of 40% recycled glass. Slag wool contains approximately 70-75% recycled content.	1 Point 1 Point in addition to MR Credit 4.1
MR Credit 5.1 (LEED-NC Only): Regional Materials: 10% Extracted, Processed & Manufactured Regionally. Use building materials or products that have been extracted, harvested or recovered, as well as manufactured, within 500 miles of the project site for a minimum of 10% (based on cost) of the total materials value. MR Credit 5.2 (LEED-NC Only): Regional Materials: 20% Extracted, Processed & Manufactured Regionally.	39 U.S. manufacturing plants and 8 Canadian plants contribute to points. Many areas in the U.S. and Canada are within 500 miles of a fiber glass or rock and slag wool plant. Most fiber glass and rock & slag wool insulation plants are in close proximity to their raw and secondary material sources.	1 Point 1 Point in addition to MR Credit 5.1
MR Credit 6 Rapidly Renewable Materials	LEED defines rapidly renewable materials as only those coming from plant material. However, sand, a key material in the manufacture of fiber glass is found abundantly in nature and replenishes itself constantly. NAIMA will be asking USGBC to expand its definitions to allow sand to be regarded as "rapidly renewable" or "renewable" as it is within the geologic community.	None at this time
Indoor Environmental Air Quality EQ Credit 3.2 LEED-NC/IEQ Credit 3 LEED-EB: Construction Indoor Air Quality (IAQ) Management Plan: Before Occupancy. The air testing option requires testing for formaldehyde and other toxins.	Fiber glass and rock & slag wool insulation may contribute to IAQ points. A wide range of products contain no formaldehyde or are certified for low emissions by GREENGUARD. Check with your LEED consultant.	1 Point
EQ Credit 7.1 LEED-NC/IEQ Credit 7.1 LEED-EB: Thermal Comfort: Design. Design building envelope to ensure occupant comfort.	Building envelope and HVAC distribution insulation are critical components for increased thermal comfort.	1 Point
Innovation & Design Process ID Credit 1-1.4 LEED-NC/IOUN Credit 1.1 LEED-EB: Innovation in Design Substantially exceed a LEED-NC performance credit such as energy performance or water efficiency. Apply strategies or measures that demonstrate a comprehensive approach and quantifiable environment and/or health benefits.	Fiber glass and rock & slag wool can be used in innovative designs that have both environmental and health benefits. Check with your LEED consultant on innovative ways to save energy and improve sound quality with insulation.	1-4 Points

LEED™ HOMES PILOT PROGRAM

Pilot Program specifications are likely to change in the near future; this chart lists current credits available with insulation.

LEED™ PREREQUISITES & CREDITS	CONTRIBUTION	POINTS
Energy & Atmosphere EA Credit 1: ENERGY STAR labeled home.	Insulation is a key part of making a home energy efficient. All insulation applies.	16 Possible Points
EA Credit 2: Insulation Must comply with Grade 2 insulation installation. Receive 1 point for having >5% efficiency in insulation or Grade 1.	Fiber glass and rock and slag wool insulation are designed to be easy to install. Proper installation is key to achieving the full R-value.	1 Point
AE 7: Water Heating Pipes and distribution must have insulation for credit.	R-4 insulation (such as fiber glass and rock and slag wool) must be used to qualify.	R-4 insulation required to qualify for all points in this category.
Materials & Resources MR Credit 3: Local Sources 90% of all materials on a checklist must come from within 500 miles of the home.	39 U.S. manufacturing plants and 8 Canadian plants contribute to points. Many areas in the US and Canada are within 500 miles of a fiber glass or rock and slag wool plant. Most fiber glass and rock & slag wool insulation plants are in close proximity to their raw material sources.	0.5 Points
MR Credit 5: Environmentally Preferable Products a) Must comply with State of California, DHS, "Practice for Testing of VOCs from Building Materials Using Small Chambers." b) Recycled Content. 100% of insulation in the house must have a minimum of 35% recycled content. c) Recycled content of 70%+.	Fiber glass contains upwards of 40% recycled glass. Slag wool contains approximately 70-75% recycled content.	0.5 Points 0.5 Points Add. 0.5 Points
Indoor Environmental Air Quality IEQ Credit 8: Contaminant Control .	Fiber glass and rock & slag wool insulation may contribute to IEQ points. A wide range of products contain no formaldehyde or are certified for low emissions by GREENGUARD. Check with your LEED consultant. (There is a parallel path given for ENERGY STAR IAQ package.)	1 Point
Innovation & Design Process ID 1: Innovation and Design.	Fiber glass and rock & slag wool can be used in innovative operation and upgrades that have both environmental and health benefits. Check with your LEED consultant on innovative ways to save energy and improve sound quality with insulation.	1-4 Points

DISCLAIMER: NAIMA can not and does not guarantee compliance with LEED through the use of its products. For advice on qualifying for LEED, work with a LEED consultant.

Fiber Glass & Rock and Slag Wool Insulation Integral Components of Sustainable Design

- **Low Embodied Energy**

Fiber glass and rock and slag wool insulation products save more than 400 trillion BTUs annually - a twelve-fold savings over the energy needed to produce these products.

been reduced, resulting in less waste at the job site and consequently, in the waste stream. In addition, more insulation can be shipped in each truck, reducing the energy required for transportation.

- **No Additional Fire Retardant Chemicals**

Fiber glass and slag wool insulations are naturally non-combustible and remain so for the life of the product. Fiber glass and slag wool require no additional fire retardant chemical treatments.

- **Recycled Content**

Many fiber glass insulation products now contain up to 40% recycled materials, depending on the plant at which they are produced. On average, slag wool insulation contains 70-75% recycled content.

About NAIMA

NAIMA is the association for North American manufacturers of fiber glass, rock wool, and slag wool insulation products. Its role is to promote energy efficiency and environmental preservation through the use of fiber glass, rock wool, and slag wool insulation, and to encourage the safe production and use of these materials.

For more information, contact:

