



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Partite 7315 Methacrylate Adhesive Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: Parson Adhesives, Inc.
Place: Rochester, MI 48309
Telephone: +1 248-299-5585
Internet: www.parsonadhesives.com
Responsible Department: sales@parsonadhesives.com

1.4. Emergency telephone number:

Chemtrec: 1-800-262-8200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: F - Highly flammable, Xi - Irritant
R phrases:
Highly flammable.
Irritating to eyes, respiratory system and skin.
May cause sensitisation by skin contact.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:
Flammable liquid: Flam. Liq. 2
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Dam. 1
Respiratory/skin sensitization: Skin Sens. 1
Specific target organ toxicity - single exposure: STOT SE 3
Specific target organ toxicity - repeated exposure: STOT RE 2
Hazard Statements:
Highly flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Hazardous components which must be listed on the label

methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate
Chlorosulfonated Polyethylene
2-methylpropenoic acid, methacrylic acid

Signal word: Danger

Pictograms: GHS02-GHS05-GHS07-GHS08



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 2 of 12



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P312	Call a POISON CENTER/doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container to in accordance with official regulations.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
201-297-1	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate	45 - 65 %
80-62-6	F - Highly flammable, Xi - Irritant R11-37/38-43	
607-035-00-6	Flam. Liq. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H225 H335 H315 H317	
	Chlorosulfonated Polyethylene	25 - 45 %
68037-39-8	Xn - Harmful R48	
	STOT RE 2; H373	
201-204-4	2-methylpropenoic acid, methacrylic acid	1 - 3 %
79-41-4	C - Corrosive, Xn - Harmful R21/22-35	
607-088-00-5	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A; H312 H302 H314	

Full text of R-, H- and EUH-phrases: see section 16.

Further Information

Product does not contain listed SVHC substances.

SECTION 4: First aid measures

4.1. Description of first aid measures



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 3 of 12

General information

In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).

After inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of irritation of the respiratory tract seek medical advice.

In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxiloson spray, Pulmicort-dosage-spray. (Auxiloson and Pulmicort are registered trademarks).

After contact with skin

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

After ingestion

Do not induce vomiting. Rinse mouth thoroughly with water. Let water be swallowed in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Foam. Water spray. Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical resistant suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray/stream to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Guide people to safety. Remove all sources of ignition. Provide adequate ventilation.

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.

Wear personal protection equipment. (refer to chapter 8)

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 4 of 12

Ventilate affected area.
Treat the assimilated material according to the section on waste disposal.
Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

refer to chapter 8.
refer to chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation.
Wear suitable protective clothing. (Refer to chapter 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. In use, may form flammable/explosive vapour-air mixture. It is possible that in the head space of sealed containers, especially in the case of thermal development, vapours of solvent cleaners may accumulate. Flames and sources of ignition must be kept well away. Heating causes rise in pressure with risk of bursting.

Further information on handling

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.
General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.
Ensure adequate ventilation of the storage area.
Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Advice on storage compatibility

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
79-41-4	Methacrylic acid	20	72		TWA (8 h)	WEL
		40	143		STEL (15 min)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

8.2. Exposure controls



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 5 of 12



Appropriate engineering controls

In case of open handling, use devices with built-in suction where possible. If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.

Protective and hygiene measures

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work. Remove contaminated clothing immediately and dispose off safely. Wash contaminated clothing prior to re-use. Used working clothes should not be used outside the work area. Street clothing should be stored separately from work clothing. Protect skin by using skin protective cream.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

Hand protection

Pull-over gloves of rubber. DIN EN 374

Suitable material:

(Breakthrough time \geq 480 min, penetration time (maximum wearing period): 160 min)

CR (polychloroprenes, Chloroprene rubber). (0,5 mm)

FKM (fluororubber). (0,4 mm)

Butyl rubber. (0,5 mm)

Before using check leak tightness / impermeability. In case of reutilization, clean gloves before taking off and store in well-aired place.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Skin protection

Suitable protection of the body: Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection required in case of:

insufficient ventilation.

exceeding critical value

Generation/formation of aerosols

Generation/formation of mist

Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Type : A / P2/P3

The filter class must be suitable for the maximum contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Environmental exposure controls

Do not empty into drains or the aquatic environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	viscous
Colour:	Off-White
Odour:	characteristic

pH-Value:

not determined

Test method

Changes in the physical state



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 6 of 12

Melting point: not determined
Initial boiling point and boiling range: Methyl-methacrylate: 100 °C
Flash point: Methyl-methacrylate: 10 °C

Explosive properties none/none

Lower explosion limits: not determined
Upper explosion limits: not determined

Oxidizing properties none/none

Vapour pressure: not determined
Density: not determined
Viscosity / dynamic: not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable under normal storage and handling conditions.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.
In use may form flammable/explosive vapour-air mixture.

10.5. Incompatible materials

Materials to avoid: Strong acid. Oxidizing agents, strong. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 7 of 12

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate					
	dermal		LD50	> 5000 mg/kg	Rabbit.	ECHA Dossier
	inhalative aerosol		LC50	29,8 mg/l	Rat.	ECHA Dossier
79-41-4	2-methylpropenoic acid, methacrylic acid					
	oral		LD50	1320 mg/kg	Rat.	ECHA Dossier
	dermal		ATE	1100 mg/kg		
	inhalative (4 h) aerosol		LC50	7,1 mg/l	Rat.	ECHA Dossier

Irritation and corrosivity

Causes skin irritation.
Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate)
Product is: sensitizing.
People who suffer from skins problems, asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

STOT-single exposure

May cause respiratory irritation. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate)

Severe effects after repeated or prolonged exposure

May cause damage to organs through prolonged or repeated exposure. (Chlorosulfonated Polyethylene) methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate (CAS-No.: 80-62-6):
Chronic oral toxicity (Rat., 104 weeks): NOAEL = >2000 mg/kg(bw)/day
Chronic inhalative toxicity (Rat., OECD 453, 104 weeks): NOEL = 500 ppm
literature information: ECHA Dossier

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.
methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate (CAS-No.: 80-62-6):
Carcinogenicity: NOAEC = >2,05 mg/l (Rat. OECD 451, 102 weeks)
Reproductive toxicity: NOAEL = 400 mg/kg(bw)/day (Rat. OECD 416)
Developmental toxicity/teratogenicity: NOAEC = >8,3 mg/l (Rat. OECD 414)
literature information: ECHA Dossier

2-methylpropenoic acid, methacrylic acid (CAS-No.: 79-41-4):
No experimental indications of mutagenicity in-vitro exist.
Reproductive toxicity: NOAEL = 400 mg/kg(bw)/day (Rat. OECD 416)
Developmental toxicity/teratogenicity: NOAEC = 350 ppm (Rat. OECD 413, 90d)
literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information

12.1. Toxicity

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate					
	Acute fish toxicity	LC50	79 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier
	Acute algae toxicity	ErC50	>110 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna	ECHA Dossier
79-41-4	2-methylpropenoic acid, methacrylic acid					
	Acute fish toxicity	LC50	85 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier
	Acute algae toxicity	ErC50	45 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EC50	>130 mg/l	48 h	Daphnia magna	ECHA Dossier
	Fish toxicity	NOEC	10 mg/l	35 d	Danio rerio	ECHA Dossier
	Crustacea toxicity	NOEC	53 mg/l	21 d	Daphnia magna	ECHA Dossier

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate			
	OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F	94%	14	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			
79-41-4	2-methylpropenoic acid, methacrylic acid			
	OECD 301D / EWG 92/69 Anhang V, C.4-E	86%	28	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate	1,32
79-41-4	2-methylpropenoic acid, methacrylic acid	0,93

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Waste disposal according to official state regulations. Consult the local waste disposal expert about waste disposal. Cleaned containers may be recycled.

Control report for waste code/ waste marking according to EAKV:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 9 of 12

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packaging in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E0
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 10 of 12

Limited quantity: 5 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Marine pollutant: NO
 Special Provisions: -
 Limited quantity: 5 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

refer to chapter 6-8

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

irrelevant

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

The preparation is dangerous in the sense of Directive 1999/45/EC.
 This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].
 Regulation 96/82/EC for danger control following severe accidents with dangerous substances:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 11 of 12

Appendix I, Part 2, No 7, (Seveso II).
REACH 1907/2006 Appendix XVII, No 3

National regulatory information

Employment restrictions: Observe employment restrictions for young people.
Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1,00, 19.03.2015, Initial release

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level

Relevant R-phrases (Number and full text)

11 Highly flammable.
21/22 Harmful in contact with skin and if swallowed.
35 Causes severe burns.
37/38 Irritating to respiratory system and skin.
43 May cause sensitisation by skin contact.
48 Danger of serious damage to health by prolonged exposure.

Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H373 May cause damage to organs (Liver.) through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Resin

Print date: 30.03.2015

Product code: 7315R

Page 12 of 12

products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Partite 7315 Methacrylate Adhesive Activator

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name: Parson Adhesives, Inc.
Place: Rochester, MI 48309
Telephone: +1 248-299-5585
Internet: www.parsonadhesives.com
Responsible Department: sales@parsonadhesives.com

1.4. Emergency telephone number:

Chemtrec: 1-800-262-8200

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: F - Highly flammable, Xi - Irritant

R phrases:

Highly flammable.

Irritating to respiratory system and skin.

May cause sensitisation by skin contact.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory/skin sensitization: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause respiratory irritation.

2.2. Label elements

Hazardous components which must be listed on the label

methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate
3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine

Signal word: Danger

Pictograms: GHS02-GHS07



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 2 of 11



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P312	Call a POISON CENTER/doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container to in accordance with official regulations.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
201-297-1	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate	65 - 85 %
80-62-6	F - Highly flammable, Xi - Irritant R11-37/38-43	
607-035-00-6	Flam. Liq. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H225 H335 H315 H317	
252-091-3	3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine	10 - 15 %
34562-31-7	Xn - Harmful, Xi - Irritant R21/22-36/37/38	
	Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H302 H312 H315 H319 H335	

Full text of R-, H- and EUH-phrases: see section 16.

Further Information

Product does not contain listed SVHC substances.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).

After inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of irregular



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 3 of 11

breathing or respiratory arrest provide artificial respiration. In case of irritation of the respiratory tract seek medical advice.

In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxilison spray, Pulmicort-dosage-spray. (Auxilison and Pulmicort are registered trademarks).

After contact with skin

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Do not induce vomiting. Rinse mouth thoroughly with water. Let water be swallowed in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Foam. Water spray. Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical resistant suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray/stream to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Guide people to safety. Remove all sources of ignition. Provide adequate ventilation.

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.

Wear personal protection equipment. (refer to chapter 8)

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the assimilated material according to the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

refer to chapter 8.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 4 of 11

refer to chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation.
Wear suitable protective clothing. (Refer to chapter 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. In use, may form flammable/explosive vapour-air mixture. It is possible that in the head space of sealed containers, especially in the case of thermal development, vapours of solvent cleaners may accumulate. Flames and sources of ignition must be kept well away. Heating causes rise in pressure with risk of bursting.

Further information on handling

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.
General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.
Ensure adequate ventilation of the storage area.
Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Advice on storage compatibility

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances or mixtures which, in contact with water emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

In case of open handling, use devices with built-in suction where possible. If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 5 of 11

Protective and hygiene measures

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work. Remove contaminated clothing immediately and dispose off safely. Wash contaminated clothing prior to re-use. Used working clothes should not be used outside the work area. Street clothing should be stored separately from work clothing. Protect skin by using skin protective cream.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

Hand protection

Pull-over gloves of rubber. DIN EN 374

Suitable material:

(Breakthrough time \geq 480 min, penetration time (maximum wearing period): 160 min)

CR (polychloroprenes, Chloroprene rubber). (0,5 mm)

FKM (fluororubber). (0,4 mm)

Butyl rubber. (0,5 mm)

Before using check leak tightness / impermeability. In case of reutilization, clean gloves before taking off and store in well-aired place.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Skin protection

Suitable protection of the body: Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection required in case of:

insufficient ventilation.

exceeding critical value

Generation/formation of aerosols

Generation/formation of mist

Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Type : A / P2/P3

The filter class must be suitable for the maximum contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Environmental exposure controls

Do not empty into drains or the aquatic environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	viscous
Colour:	Off-White / Black
Odour:	characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: Methyl-methacrylate: 100 °C

Flash point: Methyl-methacrylate: 10 °C

Explosive properties

none/none

Lower explosion limits: not determined



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 6 of 11

Upper explosion limits: not determined

Oxidizing properties
none/none

Vapour pressure: not determined

Density: not determined

Viscosity / dynamic: not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable under normal storage and handling conditions.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.
In use may form flammable/explosive vapour-air mixture.

10.5. Incompatible materials

Materials to avoid: Strong acid. Oxidizing agents, strong. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate	dermal	LD50	> 5000 mg/kg	Rabbit.	ECHA Dossier
		inhalative aerosol	LC50	29,8 mg/l	Rat.	ECHA Dossier
34562-31-7	3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine	oral	ATE	500 mg/kg		
		dermal	ATE	1100 mg/kg		

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 7 of 11

May cause an allergic skin reaction. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate)

Product is: sensitizing.

People who suffer from skins problems, asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

STOT-single exposure

May cause respiratory irritation. (methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate), (3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate (CAS-No.: 80-62-6):

Chronic oral toxicity (Rat., 104 weeks): NOAEL = >2000 mg/kg(bw)/day

Chronic inhalative toxicity (Rat., OECD 453, 104 weeks): NOEL = 500 ppm

literature information: ECHA Dossier

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate (CAS-No.: 80-62-6):

Carcinogenicity: NOAEC = >2,05 mg/l (Rat. OECD 451, 102 weeks)

Reproductive toxicity: NOAEL = 400 mg/kg(bw)/day (Rat. OECD 416)

Developmental toxicity/teratogenicity: NOAEC = >8,3 mg/l (Rat. OECD 414)

literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate					
	Acute fish toxicity	LC50	79 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier
	Acute algae toxicity	ErC50	>110 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna	ECHA Dossier

12.2. Persistence and degradability

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate				
	OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F	94%	14	ECHA Dossier	
	Easily biodegradable (concerning to the criteria of the OECD)				

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate	1,32



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 8 of 11

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Waste disposal according to official state regulations. Consult the local waste disposal expert about waste disposal. Cleaned containers may be recycled.

Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packaging in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Limited quantity:	5 L



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 9 of 11

Excepted quantity: E0
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: NO
Special Provisions: -
Limited quantity: 5 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 10 of 11

IATA-max. quantity - Cargo:

60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

refer to chapter 6-8

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

irrelevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

The preparation is dangerous in the sense of Directive 1999/45/EC.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

Regulation 96/82/EC for danger control following severe accidents with dangerous substances: Appendix I, Part 2, No 7, (Seveso II).

REACH 1907/2006 Appendix XVII, No 3

National regulatory information

Employment restrictions:

Observe employment restrictions for young people.

Water contaminating class (D):

1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1,00, 19.03.2015, Initial release

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

Relevant R-phrases (Number and full text)

- | | |
|----------|--|
| 11 | Highly flammable. |
| 21/22 | Harmful in contact with skin and if swallowed. |
| 36/37/38 | Irritating to eyes, respiratory system and skin. |
| 37/38 | Irritating to respiratory system and skin. |
| 43 | May cause sensitisation by skin contact. |



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Partite 7315 Methacrylate Adhesive Activator

Print date: 30.03.2015

Product code: 7315A

Page 11 of 11

Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)