

A mineral fiber panel with high impact resistance and high light reflectance, ideal in educational settings.




APPLICATIONS

- Schools
- Dorms
- Day Care Centers
- Corridors
- Commercial Interior Spaces
- Other Commercial Buildings / Space Applications

FEATURES AND BENEFITS

- Up to 25% higher surface hardness than conventional wet-felted ceiling products per ASTM C 367 testing
- Environmental Product Declaration (EPD) available for this product
- Available in fire-rated (Protectone) versions
- Shares surface pattern with other Fine Fissured products
- Health Product Declaration (HPD) available for this product

SUSPENSION SYSTEM OPTIONS



Trim
15/16 Grid

LEED® v4	
RECYCLED CONTENT	
CLASS A PROTECTONE®	33%
	44%
<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input type="checkbox"/>	EQ: Acoustic Performance
<input type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials
<input checked="" type="checkbox"/>	EQ: Daylight
<input checked="" type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.



All products in this line feature these attributes:



SAG RESISTANT



BIOSHIELD® MOLD/MILDEW RESISTANT



LR 0.84



EPD AVAILABLE



HPD AVAILABLE




LOW VOC EMISSION COMPLIANT CERTIFIED



RECYCLED CONTENT 33-44%

SCHOOL BOARD

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	UL Fire-Rated	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
TRIM												
	NRC 55	FFSB-157	Panels	24 x 24 x 5/8	0.55	35	33%	—	16	64	47	20
		FFSB-197	Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	47	20
		PFFSB-157	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	72	20
		PFFSB-197	Panels	24 x 48 x 5/8	0.55	40	44%	Yes*	8	64	72	20

* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL
Mineral Fiber

ASTM E1264 CLASSIFICATION
Type III, Form 2, Pattern C D

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE
BioShield treatment included for added mold and mildew resistance.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY
10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/ceilings.



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com