

The Symphony f Rx line provides a white, clean, monolithic ceiling visual. Superior stain resistance and water repellency make this product ideal for healthcare and kitchen applications.




**APPLICATIONS**

- Patient and Treatment Rooms
- Emergency Rooms and Nurses' Stations
- Semi-Restricted Surgical Areas
- Kitchen / Food Prep Areas
- Corridors
- Restrooms
- Other Commercial Buildings / Space Applications

**FEATURES AND BENEFITS**

- Superior sound absorption (NRC 0.95)
- Superior stain resistance and water repellency
- Washable with most sanitizing solutions and wash-tested to 2,000 wash cycles
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- Approved for use in federally registered Canadian food establishments
- Certified VOC compliant

**SUSPENSION SYSTEM OPTIONS**



Trim  
15/16 Grid

Reveal  
15/16 Grid

Narrow Reveal  
9/16 Grid

Narrow Reveal  
9/16 Grid Bolt Slot

**LEED® v4**

**RECYCLED CONTENT** 29 – 31%

- ✓ EA: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.



EPD Available



HPD Available

# SYMPHONY® f Rx

Smooth  
Fiberglass

All products in this line feature these attributes:



SAG RESISTANT



MOLD/MILDEW RESISTANT INHERENT



LR 0.90



WASHABLE w/SANITIZING CHEMICALS



EPD AVAILABLE



HPD AVAILABLE



LOW VOC EMISSION COMPLIANT CERTIFIED



RECYCLED CONTENT 29-31%

## SYMPHONY f Rx

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>											
	NRC 95	1342-RXS-1	Panels	24 x 24 x 1	0.95	—	31%	24	96	34	14
		1340-RXS-1	Panels	24 x 48 x 1	0.95	—	31%	12	96	34	14
<b>REVEAL</b>											
	NRC 95	1342B-RXS-1	Panels	24 x 24 x 1	0.95	—	29%	24	96	42	14
		1340B-RXS-1	Panels	24 x 48 x 1	0.95	—	29%	12	96	42	14
<b>NARROW REVEAL</b>											
	NRC 95	1342F-RXS-1	Panels	24 x 24 x 1	0.95	—	29%	24	96	34	14
		1340F-RXS-1	Panels	24 x 48 x 1	0.95	—	29%	12	96	42	14

CAC range of 24-25 achieved with CAC foil backing. CAC Foil Backing is available for the Symphony f Rx line as a special order.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

## ACCESSORIES

SYMPHONY f Rx ACCESSORIES	Product Name	Pieces/carton	Use	
	1400-SEL-1	Fiberglass Edge Sealant	1	For re-sealing cut edges; 1 quart container

## PHYSICAL DATA

**MATERIAL**  
Fiberglass

**ASTM E1264 CLASSIFICATION**  
Type XII, Form 2, Pattern E

**FIRE CLASS (ASTM E1264)**  
All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

**MOLD/MILDEW RESISTANCE**  
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

**VOC EMISSIONS**  
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017

**MAINTENANCE**  
Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

**WARRANTY**  
10-year 104/95 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/ceilings](http://certainteed.com/ceilings).



**CertainTeed**

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM  
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)