



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 19, 2019

1 Identification

- Product identifier
- · Trade name: Type X/Type C Gypsum Board
- · Other product identifiers:
- 1/2" Type C 1/2" Abuse Resistant Type C
- 5/8" Abuse Resistant Type X
- 5/8" Evenwall Type X
- 5/8" Exterior Soffit Type C
- 5/8" Exterior Soffit Type X
- 5/8" Extreme Abuse Type X
- 5/8" Extreme Impact Type X5/8" Type X
- 5/8" Sheathing Treated Core Type X
- 5/8" Type C
- 5/8" Veneer Plaster Base Type C
- 5/8" Veneer Plaster Base Type X
- · Recommended use and restriction on use
- Recommended use: Gypsum panel products for interior and exterior wall applications.
- · Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

CertainTeed Gypsum

20 Moores Road

Malvern, PA 19355

Professional: 800-233-8990 Consumer: 800-782-8777

www.certainteed.com

Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

1-300-954-583 (Australia)

0-800-591-6042 (Brazil)

400-120-0751 (China)

000-800-100-4086 (India)

01-800-099-0731 (Mexico)

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- Other hazards There are no other hazards not otherwise classified that have been identified.

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 19, 2019

Trade name: Type X/Type C Gypsum Board

(Cont'd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:		
9004-34-6	cellulose	<10%
8002-74-2	Paraffin waxes and Hydrocarbon waxes	<5%

4 First-aid measures

- Description of first aid measures
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Brush off loose particles from skin.

Wash with soap and water.

Seek medical treatment in case of complaints.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Coughing

· Indication of any immediate medical attention and special treatment needed:

No relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 19, 2019

Trade name: Type X/Type C Gypsum Board

(Cont'd. of page 2)

Avoid formation of dust.

Do not breathe dust.

- · Environmental precautions No special measures required.
- · Methods and material for containment and cleaning up

Sweep up and place into an appropriate container.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- Precautions for safe handling:

Prevent formation of dust.

Avoid breathing dust.

Handle with care.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Storage area should be dry and well-ventilated.

Avoid storage near extreme heat, ignition sources or open flame.

- · Information about storage in one common storage facility: Protect from humidity and water.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

Control parameters						
· Components with limit values that require monitoring at the workplace:						
9004-34-6 cellulose						
PEL (USA) Long-term value: 15* 5** mg/m³ *total dust **respirable fraction						
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction					
TLV (USA)	Long-term value: 10 mg/m³					
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction					
EV (Canada)	Long-term value: 10 mg/m³ paper fibre, total dust					
LMPE (Mexico)	Long-term value: 10 mg/m³					
8002-74-2 Para	8002-74-2 Paraffin waxes and Hydrocarbon waxes					
REL (USA)	Long-term value: 2 mg/m³					
TLV (USA)	Long-term value: 2 mg/m³					
EL (Canada)	Long-term value: 2 mg/m³					
	(Cont'd. on page					

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 19, 2019

Trade name: Type X/Type C Gypsum Board

EV (Canada) Long-term value: 2 mg/m³ fume

LMPE (Mexico) Long-term value: 2 mg/m³

Exposure controls

- · General protective and hygienic measures: Avoid breathing dust.
- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Use respiratory protection when grinding or cutting material.

Particulate mask should filter at least 99% of airborne particles.

· Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear gloves for the protection against mechanical hazards according to OSHA and NIOSH rules.

- Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.
- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

Physical and chemical properties					
Information on basic physical and chemical properties					
Appearance:					
Form:	Solid				
Color:	White				
Odor:	Odorless				
Odor threshold:	Not determined.				
pH-value:	Not applicable.				
Melting point/Melting range:	Not determined.				
Boiling point/Boiling range:	Not determined.				
Flash point:	Not applicable.				
Flammability (solid, gaseous):	Product is not flammable.				
Auto-ignition temperature:	Not determined.				
Decomposition temperature:	1450 °C (2642 °F)				
Danger of explosion:	Product does not present an explosion hazard.				
Explosion limits					
Lower:	Not determined.				
Upper:	Not determined.				
Oxidizing properties:	Non-oxidizing.				
Vapor pressure:	Not applicable.				
Density:					
Relative density:	Not determined.				
Vapor density:	Not applicable.				
		(Cont'd. on pag			

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 19, 2019

Trade name: Type X/Type C Gypsum Board

(Cont'd. of page 4)

Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Not applicable. Kinematic: Not applicable.

• Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: The product is non-reactive under normal conditions of use, storage and transport.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Moisture.
- · Incompatible materials No relevant information available.
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Sulfur oxides (SOx)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- Sensitization: Based on available data, the classification criteria are not met.
- · IARC (International Agency for Research on Cancer):

Present in trace quantities.

14808-60-7 Quartz (SiO2)

1

NTP (National Toxicology Program):

Present in trace quantities.

14808-60-7 Quartz (SiO2)

K

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Inhalation.

Eye contact.

Skin contact.

(Cont'd. on page 6)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 19, 2019

Trade name: Type X/Type C Gypsum Board

(Cont'd. of page 5)

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Smaller quantities can be disposed of with household waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- Recommendation: Disposal must be made according to official regulations.

14 Transport information					
· UN-Number					
· DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.				
· UN proper shipping name · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.				
· Transport hazard class(es)					
· DOT, ADR/RID/ADN, IMDG, IATA · Class	Not regulated.				
· Packing group · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.				
· Environmental hazards · Marine pollutant:	No				
· Special precautions for user	Not applicable.				
		(Cont'd. on page 7)			

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 19, 2019

Trade name: Type X/Type C Gypsum Board

(Cont'd. of page 6)

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- Chemicals known to cause cancer:

Present in trace quantities.

14808-60-7 Quartz (SiO2)

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

Present in trace quantities.

14808-60-7 Quartz (SiO2)

11

· Canadian Domestic Substances List (DSL): (Substances not listed.)

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

(Cont'd. on page 8)

Page: 8/8

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 19, 2019

Trade name: Type X/Type C Gypsum Board

(Cont'd. of page 7)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com