

SUBMITTAL SHEET

HEARTFELT®

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE Felt: Non-woven PES fibres

PROFILE

HeartFelt Linear: 4OHL55 40mm x 55mm (1-9/16" x 2-3/16")
 4OHL80 40mm x 80mm (1-9/16" x 3-1/8")
 4OHL105 40mm x 105mm (1-9/16" x 4-1/8")

HeartFelt Round: 4OHR64 40mm x 64mm (1-9/16" x 2-1/2")

PANEL COLOUR/FINISH

HeartFelt - Greys White - #7593F Dark Grey - #7598F
 Light Grey - #7596F Black - #7594F
 Medium Grey - #7597F

HeartFelt - Earth Tones Creme - #7575F Light Brown - #7576F
(4OHL55 only) Medium Brown - #7577F Dark Brown - #7578F
 Umber - #7579F

PANEL DEPTH Depth: 55mm, 64mm, 80mm, 105mm: _____

CARRIERS

Standard Carrier

- 60mm 60mm (2-3/8") o.c. module, 21mm (13/16") reveal
- 80mm 80mm (3-1/8") o.c. module, 40mm (1-9/16") reveal
- 100mm 100mm (3-15/16") o.c. module, 60mm (2-3/8") reveal

Carrier for HeartFelt - Levels

- Wave
- Choppy
- Step
- Scatter
- Custom* _____

* Custom carrier modulations are available upon request. HeartFelt Levels, 50mm (2"), 70mm (2-3/4"), and 90mm (3-1/2") spacings, as well additional configurations and spacings are available. An additional lead time will apply. Please contact your local sales representative for more information.

CARRIERS COLOUR/FINISH Silver - #7178
 Painted Black - #1863
 Other: _____

EXPOSURE Interior Only

HeartFelt® is a registered trademark of Hunter Douglas, Inc. used with permission.

To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.233.8990
www.certainteed.ca/architectural

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

CertainTeed Architectural Products, a division of CertainTeed Canada, Inc.

SOUND ABSORPTION (NRC) SUMMARY*

Panel Spacing	Open Area	Reveal	Acoustics
60 mm (2-3/8")	33%	21 mm (13/16")	NRC 0.60
80 mm (3-1/8")	50%	40 mm (1-9/16")	NRC 0.50
100 mm (3-15/16")	59%	60 mm (2-3/8")	NRC 0.45

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: Non-woven PES fibres

Warranty: 1 year limited

Seismic rating: Class A,B,C,D,E,F

Fire rating: Rated per CAN/ULC S102

Weight: Varies

Wind load: N/A

Light reflectance (LR): Varies with colour selected

Given the unique and special nature of our HeartFelt® ceiling product, steps should be taken (before and during installation, as well as over the lifetime of the ceiling) to avoid or minimize static and the accumulation of dust, lint, dirt or airborne particles on or around the felt. Manufacturer does not warrant against or take responsibility for any such static or accumulation.